

## RUST CONVERTER SPRAY

Based on acrylic resin penetrates rust, stops the growth of rust and permanently seals the surface, making it suitable as a substrate for additional coatings. For applications in the automotive, construction and agricultural machinery sectors as well as industry and handicraft.

### CHARACTERISTICS

- compatible with all sorts of material
- high penetrative ability
- resistant to water, salt water, as well as weak acids and bases
- very good adhesion, so primers are unnecessary
- silicone-free

### TECHNICAL DATA

processing temperature	+5°C to +25°C
temperature resistance	-40°C to +80°C
shelf life	36 months; store in a cool and dry place

### INSTRUCTIONS FOR USE

Shake well before use. Remove coarse excess material with a wire brush and then thoroughly clean and degrease with PETEC brake cleaner (art. no. 70060). Spray PETEC rust converter spray onto the corroded area and leave to take effect for approx. 7 minutes. Perform this process a second time, and a third if necessary. After 14 hours, it will be possible to coat over the area. Do not use on plastics or paints/varnishes. Coatings should only be applied using suitable products and once the surface has fully cured. Paints, varnishes or other media containing solvents may inhibit or ruin the curing process. Always carry out tests in order to ensure the suitability of the product for the application in question. After use, turn the can upside down and spray until the valve is empty.

Observe the safety and technical datasheet! (Download PETEC data sheets from [www.petec.de](http://www.petec.de))

### CONTAINER SIZE



Item-No. 70040

500 ml spray