

Printing date 14.11.2016 Version number 37 Revision: 11.10.2016

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: PETEC Zinc-Aluminium Spray
- · Article number: 71050
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Lacquer
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

PETEC Verbindungstechnik GmbH

Wüstenbuch 26

96132 Schlüsselfeld / Deutschland

Telefon +49 (0) 9555 80994-0

Fax +49 (0) 9555 80994-25

Homepage www.petec.de

E-Mail: info@petec.de

- · Further information obtainable from: Technische Auskunft: info@petec.de
- 1.4 Emergency telephone number: Telefon +49 (0) 9555 80994-0

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	Н336	May cause drowsiness or dizziness.
Asp. Tox. 1	Н304	May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

GHS09

· Signal word Danger

(Contd. on page 2)



Version number 37 Revision: 11.10.2016 Printing date 14.11.2016

Trade name: PETEC Zinc-Aluminium Spray

(Contd. of page 1)

#### · Hazard-determining components of labelling:

Hydrocarbons, C9, aromatics

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

*Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane* 

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P211 Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use. P251 Avoid breathing vapours or spray. P261

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P391 Collect spillage.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 Dispose of contents/container to hazardous or special waste collection point.

#### · Additional information:

EUH208 Contains 2-butanone oxime. May produce an allergic reaction. Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · vPvB: Not applicable.

#### SECTION 3: Composition/information on ingredients

#### · 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2	acetone Flam. Liq. 2, H225; Use Irrit. 2, H319; STOT SE 3, H336	20-<25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane	10-<20%
CAS: 115-10-6 EINECS: 204-065-8	dimethyl ether	10-<20%
·	(Co	ontd. on page 3)



Printing date 14.11.2016 Version number 37 Revision: 11.10.2016

Trade name: PETEC Zinc-Aluminium Spray

CAS: 1330-20-7	xylene	10-<20%
EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	(A) Flam. Liq. 3, H226; (D) Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220; Press. Gas C, H280	5-<10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	Hydrocarbons, C9, aromatics ❖ Asp. Tox. 1, H304; ❖ Aquatic Chronic 2, H411; ❖ STOT SE 3, H335-H336	5-<10%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33-xxxx	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes ♠ Flam. Liq. 2, H225; ♠ Asp. Tox. 1, H304; ♠ Aquatic Chronic 2, H411; ♠ Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane  Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
CAS: 7440-66-6 EINECS: 231-175-3 Reg.nr.: 01-2119467174-37-xxxx	zinc powder -zinc dust (stabilized)  Aquatic Acute 1, H400; Aquatic Chronic 1, H410	2.5-<5%
EINECS: 231-072-3 Reg.nr.: 01-2119529243-45-xxxx	aluminium powder (stabilized)  Flam. Sol. 2, H228; Water-react. 2, H261	2.5-<5%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane  Flam. Gas 1, H220; Press. Gas C, H280	2.5-<5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 02-2119752523-40-xxxx	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	1.0-<2.5%
CAS: 96-29-7 EINECS: 202-496-6 Reg.nr.: 01-2119539477-28-xxxx	2-butanone oxime © Carc. 2, H351; © Eye Dam. 1, H318; ① Acute Tox. 4, H312; Skin Sens. 1, H317	0.1-<1.0%

<sup>3</sup> J

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- $\cdot$  After inhalation:

Supply fresh air; consult doctor in case of complaints.

Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty

Headache

Dizziness

Dizziness

Coughing

Nausea

(Contd. on page 4)



Printing date 14.11.2016 Version number 37 Revision: 11.10.2016

Trade name: PETEC Zinc-Aluminium Spray

(Contd. of page 3)

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

Later observation for pneumonia and pulmonary oedema.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- $\cdot$  5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

• **6.4 Reference to other sections** See Section 13 for disposal information.

#### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin and eyes.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.

(Contd. on page 5)





Printing date 14.11.2016 Version number 37 Revision: 11.10.2016

Trade name: PETEC Zinc-Aluminium Spray

(Contd. of page 4)

 $\cdot$  7.3 *Specific end use(s) No further relevant information available.* 

#### SECTION 8: Exposure controls/personal protection

- $\cdot \textbf{\textit{Additional information about design of technical facilities:}} \ \textit{No further data; see item 7.}$
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

CAS: 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

CAS: 1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

CAS: 106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

CAS: 100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk

· Ingredients with biological limit values:

CAS: 1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

 $Do \ not \ inhale \ gases \, / \, fumes \, / \, aerosols.$ 

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · Recommended filter device for short term use: Filter AX
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Butyl rubber, BR

(Contd. on page 6)





Printing date 14.11.2016 Version number 37 Revision: 11.10.2016

Trade name: PETEC Zinc-Aluminium Spray

(Contd. of page 5)

Recommended thickness of the material:  $\geq 0.7 \text{ mm}$ 

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

#### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol Colour: Silver-coloured · Odour: Solvent-like

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· Flash point: Not applicable, as aerosol.

· Ignition temperature: >200 °C

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

· Explosion limits:

Not determined. Lower: Not determined. Upper: Not determined.

· Vapour pressure:

· Density at 20 °C: 0.73485 g/cm<sup>3</sup>

· Solubility in / Miscibility with

Not miscible or difficult to mix. water:

· Viscosity:

Dynamic: Not determined. Not determined. Kinematic: 88.5 % Organic solvents:

VOC (EC) 650.6 g/l

· 9.2 Other information No further relevant information available.

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 7)





Printing date 14.11.2016 Version number 37 Revision: 11.10.2016

Trade name: PETEC Zinc-Aluminium Spray

(Contd. of page 6)

- $\cdot$  10.4 Conditions to avoid No further relevant information available.
- $\cdot$  10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

		toxicological effects
		on available data, the classification criteria are not met.
		vant for classification:
	-	Estimates)
	LD50	18977 mg/kg (rabbit)
Inhalative	LC50/4 h	162 mg/l
CAS: 67-6	4-1 aceton	e
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (rat)
CAS: 75-2	8-5 isobute	ane
		>50 mg/l (rat)
CAS: 115-		
		308 mg/l (rat)
CAS: 1330	-	
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.7 mg/l (rat)
CAS: 74-9		
Inhalative	LC50/4 h	20 mg/l (rat)
Hydrocarb	ons, C9, a	romatics
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Hydrocarb	ons, C7, n	-alkanes, isoalkanes, cycloalkanes
Oral	LD50	>5840 mg/kg (rat)
Dermal	<i>LD50</i>	>2920 mg/kg (rat)
		>23.3 mg/l (rat)
		7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane
Oral	<i>LD50</i>	>5840 mg/kg (rat)
Dermal	<i>LD50</i>	>2920 mg/kg (rat)
		<25.2 mg/l (rat)
CAS: 106-		
		658 mg/l (rat)
CAS: 100-		
Oral	<i>LD50</i>	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)



Printing date 14.11.2016 Version number 37 Revision: 11.10.2016

Trade name: PETEC Zinc-Aluminium Spray

(Contd. of page 7)

 Oral
 LD50
 3700 mg/kg (rat)

 Dermal
 LD50
 200-2000 mg/kg (rat)

 Inhalative
 LC50/4 h
 20 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- $\cdot \textit{Reproductive toxicity Based on available data, the classification criteria are not met.} \\$
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

#### **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic	toxicity:
-----------	-----------

CAS: 67-64-1 acetone

EC50/48 h | 8800 mg/l (daphnia)

CAS: 1330-20-7 xylene

EC50/48 h 165 mg/l (daphnia)

Hydrocarbons, C9, aromatics

LC50 1-10 mg/l (daphnia)

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

EC50/48 h 3 mg/l (daphnia)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane

EC50/48 h 3 mg/l (daphnia)

CAS: 100-41-4 ethylbenzene

EC50/48 h 2.1 mg/l (daphnia)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 9)



Printing date 14.11.2016 Version number 37 Revision: 11.10.2016

Trade name: PETEC Zinc-Aluminium Spray

(Contd. of page 8)

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

16 05 04\* gases in pressure containers (including halons) containing hazardous substances

15 01 04 metallic packaging

· Uncleaned packaging:

· Class

· Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR,RID,ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR/RID/ADN	UN1950 AEROSOLS, ENVIRONMENTALL HAZARDOUS
· IMDG	AEROSOLS, MARINE POLLUTANT
IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN	
· Class · Label	2 5F Gases. 2.1
· IMDG	
· Class	2.1

2.1



Printing date 14.11.2016 Version number 37 Revision: 11.10.2016

Trade name: PETEC Zinc-Aluminium Spray

	(Contd. of page
· Label	2.1
· 14.4 Packing group · ADR,RID,ADN, IMDG, IATA	Void
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances zinc powder-zinc dust (pyrophoric)
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR/RID/ADN):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Gases.
· Danger code (Kemler):	-
· EMS Number:	F- $D$ , $S$ - $U$
· Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre
	Category A. For AEROSOLS with a capacity above 1 litre
	Category B. For WASTE AEROSOLS: Category C, Clea
a	of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litro
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4. For AEROSOLS with a capacit
	above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS
	Segregation as for the appropriate subdivision of class 2.
7.5	
· 14.7 Transport in bulk according to Anne Marpol and the IBC Code	x 11 of Not applicable.
	ты иррисиоте.
· Transport/Additional information:	
· ADR/RID/ADN	17
· Limited quantities (LQ)	1L Code: E0
· Excepted quantities (EQ)	
· Transport category	Not permitted as Excepted Quantity 2
· Tunnel restriction code	D D
	υ 
· IMDG	17
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALL
	HAZARDOUS

#### **SECTION 15: Regulatory information**

- $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 11)



Printing date 14.11.2016 Version number 37 Revision: 11.10.2016

Trade name: PETEC Zinc-Aluminium Spray

(Contd. of page 10)

- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 28, 29
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H261 In contact with water releases flammable gases.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Flam. Sol. 2: Flammable solids – Category 2

Water-react. 2: Substances and mixtures which in contact with water emit flammable gases – Category 2

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2





Printing date 14.11.2016 Version number 37 Revision: 11.10.2016

Trade name: PETEC Zinc-Aluminium Spray

(Contd. of page 11)

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

\* Data compared to the previous version altered.

ar -