

HIGH TEMPERATURE MULTI-ASSEMBLY PASTE

Ceramic-based, can be applied using a brush as a lubricating, release and corrosion protection agent.

CHARACTERISTICS

- long-lasting agent for lubricating, sliding and separating
- very high corrosion protection
- temperature resistant from -40°C to $+1500^{\circ}\text{C}$
- very good adhesion
- resistant to high pressure
- metal-free lubricant, no interference of sensors in braking systems
- prevents braking and creaky noises

TECHNICAL DATA

colour	creme
density	approx. $1\text{g}/\text{cm}^3$
temperature resistance	-40°C to $+1500^{\circ}\text{C}$
shelf life	36 months; store in a cool and dry place

INSTRUCTIONS FOR USE

Remove coarse excess material with a wire brush and then thoroughly clean and degrease with PETEC brake cleaner (art. no. 70060). Apply an even coat of PETEC high-temperature multi-assembly paste with a brush on the stressed threads and surfaces. Then assemble the parts as required. Note: Do not apply to the brake disc or the friction side of the brake pad.

Observe the safety and technical datasheet! (Download PETEC data sheets from www.petec.de)

CONTAINER SIZE

	
Item-No. 94420	Item-No. 94422
200 ml can	6 x 200 ml can