

## K&D BODY ADHESIVE AND SEALANT

Fast curing, elastic single-component adhesive and sealant on a polyurethane base, which hardens due to humidity.

### CHARACTERISTICS

- wide adhesion spectrum, strong adhesion
- capable of sealing gaps of different sizes
- permanent sealing effect, permanently elastic and vibration-resistant
- can be re-coated, silicone free, weatherproof and UV-resistant
- non-corrosive, resistant to diluted acids and alkali solutions

### TECHNICAL DATA

<b>colour</b>	white, grey, black
<b>temperature resistance</b>	-40°C to +90°C
<b>processing temperature</b>	+5°C to +35°C
<b>processing time</b>	10 – 15 minutes
<b>curing time (at +22°C)</b>	approx. 4 mm/24 hours (depending on temperature and coat thickness)
<b>processing time</b>	10 – 15 minutes
<b>shelf life</b>	18 months (original packaging); store in a cool and dry place

### INSTRUCTIONS FOR USE

Thoroughly clean and degrease the surfaces with PETEC Multi Cleaner (art. no. 82100 or 82200). Remove the cap, pierce the film, cut the nozzle and screw on. Apply the product using an applicator gun and bond. Surplus material can be removed with PETEC Multi Cleaner. Only after complete curing can K & D be re-coated with suitable products. Paints, varnishes or other media containing solvents may inhibit or ruin the curing process. Always carry out tests in order to ensure the suitability of the product for the application in question.

Observe the safety and technical datasheet! (Download PETEC data sheets from [www.petec.de](http://www.petec.de))

### CONTAINER SIZE

		
<b>Item-No. 94530</b>	<b>Item-No. 94630</b>	<b>Item-No. 94730</b>
310 ml cartridge	310 ml cartridge	310 ml cartridge