### Safety data sheet

BINDUNGEN

according to 1907/2006/EC, Article 31

Printing date 14.11.2016 Version number 58 Revision: 02.11.2016 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: PETEC High-Performance PTFE-Spray · Article number: 74050 · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Lubricant · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: PETEC Verbindungstechnik GmbH Wüstenbuch 26 96132 Schlüsselfeld / Deutschland Telefon +49 (0) 9555 80994-0 Fax +49 (0) 9555 80994-25 Homepage www.petec.de E-Mail: info@petec.de • Further information obtainable from: Technische Auskunft: info@petec.de · 1.4 Emergency telephone number: Telefon +49 (0) 9555 80994-0 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. GHS07 Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 GHS07 · Signal word Danger · Hazard-determining components of labelling: Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane · Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. (Contd. on page 2)



Printing date 14.11.2016

# Safety data sheet according to 1907/2006/EC, Article 31

Version number 58

Revision: 02.11.2016

Trade name: PETEC High-Performance PTFE-Spray

(Contd. of page 1) H412 Harmful to aquatic life with long lasting effects. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing vapours or spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves. Call a POISON CENTER/doctor if you feel unwell. *P312* P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 Dispose of contents/container to hazardous or special waste collection point. · Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane The second s	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane 🚸 Flam. Gas 1, H220; Press. Gas C, H280	25-<50%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33-xxxx	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane Flam. Gas 1, H220; Press. Gas C, H280	5-<10%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

#### • 4.1 Description of first aid measures

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Take affected persons into fresh air and keep quiet.

#### • After skin contact:

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)



# Safety data sheet according to 1907/2006/EC, Article 31

Version number 58

Revision: 02.11.2016

Trade name: PETEC High-Performance PTFE-Spray

 $(Contd. \ of \ page \ 2)$ 

Immediately remove any clothing soiled by the product.

· After eye contact:

Printing date 14.11.2016

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.
 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty Headache Dizziness Dizziness Coughing

Nausea

• **4.3 Indication of any immediate medical attention and special treatment needed** If swallowed or in case of vomiting, danger of entering the lungs. Later observation for pneumonia and pulmonary oedema.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Foam Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- Formation of toxic gases is possible during heating or in case of fire.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information
- Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
  6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- 6.4 Reference to other sections See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Avoid contact with skin and eyes.

(Contd. on page 4)

GB



### Safety data sheet according to 1907/2006/EC, Article 31

Version number 58 Revision: 02.11.2016 Printing date 14.11.2016 Trade name: PETEC High-Performance PTFE-Spray (Contd. of page 3) · Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use. · 7.2 Conditions for safe storage, including any incompatibilities · Storage: • Requirements to be met by storerooms and receptacles: Observe official regulations on storing packagings with pressurised containers. · Information about storage in one common storage facility: Not required. · Further information about storage conditions: Protect from heat and direct sunlight. · 7.3 Specific end use(s) No further relevant information available. **SECTION 8: Exposure controls/personal protection** · Additional information about design of technical facilities: No further data; see item 7. · Ingredients with limit values that require monitoring at the workplace: CAS: 106-97-8 butane WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) · Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls · Personal protective equipment: · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. · Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Use suitable respiratory protective device in case of insufficient ventilation. • Recommended filter device for short term use: Filter AX · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. · Material of gloves Nitrile rubber, NBR (EN 374) Recommended thickness of the material:  $\geq 0.45$  mm · Penetration time of glove material ≥240 min The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

GB



Page 5/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.11.2016

Version number 58

Revision: 02.11.2016

Trade name: PETEC High-Performance PTFE-Spray

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

(EN 166)

• *Body protection: Protective work clothing* 

(EN 13034-6)

<b>SECTION</b>	9: Physical	and chemical	properties
	~		<b>1 1</b>

· General Information		
· Appearance:		
Form:	Aerosol	
Colour:	Whitish	
· Odour:	Petrol-like	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	<0 °C	
· Flash point:	Not applicable, as aerosol.	
· Flammability (solid, gaseous):	Extremely flammable liquefied gas.	
· Ignition temperature:	>200 °C	
• Decomposition temperature:	Not determined.	
· Self-igniting:	Not determined.	
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapou. mixtures are possible.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapour pressure:	Not determined.	
· Density at 20 °C:	0.60191 g/cm <sup>3</sup>	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Organic solvents:	92.5 %	
VOC (EC)	556.9 g/l	

GB



Page 6/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.11.2016

Version number 58

Revision: 02.11.2016

Trade name: PETEC High-Performance PTFE-Spray

(Contd. of page 5)

• 9.2 Other information

No further relevant information available.

### **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

· 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products:

Aldehyde

Carbon monoxide and carbon dioxide

### **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h 79.4 mg/l (rat)

CAS: 75-28-5 isobutane

Inhalative LC50/4 h >50 mg/l (rat)

CAS: 74-98-6 propane

Inhalative LC50/4 h 20 mg/l (rat)

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

Oral LD50 >5840 mg/kg (rat)

Dermal LD50 >2920 mg/kg (rat)

Inhalative LC50/4 h > 23.3 mg/l (rat)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane

Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rat)
Inhalative	LC50/4 h	<25.2 mg/l (rat)

CAS: 106-97-8 butane

Inhalative LC50/4 h 658 mg/l (rat)

• Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

• Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB



Page 7/9

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.11.2016

Version number 58

Revision: 02.11.2016

Trade name: PETEC High-Performance PTFE-Spray

(Contd. of page 6)

· Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

EC50/48 h 3 mg/l (daphnia)

*Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane* 

*EC50/48 h* 3 *mg/l* (*daphnia*)

· 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:
- Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

- Danger to drinking water if even small quantities leak into the ground.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

16 05 04\* gases in pressure containers (including halons) containing hazardous substances

15 01 04 metallic packaging

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number		
ADR,RID,ADN, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name		
ADR/RID/ADN	UN1950 AEROSOLS	
·IMDG	AEROSOLS	
·IATA	AEROSOLS, flammable	



Page 8/9

GB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.11.2016 Version number 58 Revision: 02.11.2016 Trade name: PETEC High-Performance PTFE-Spray (Contd. of page 7) · 14.3 Transport hazard class(es) · ADR/RID/ADN · Class 2 5F Gases. · Label 2.1 · IMDG, IATA 2.1 · Class 2.1 · Label · 14.4 Packing group Void · ADR, RID, ADN, IMDG, IATA · 14.5 Environmental hazards: • Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. · Danger code (Kemler): · EMS Number: F-D, S-USW1 Protected from sources of heat. · Stowage Code SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: · Segregation Code Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · ADR/RID/ADN · Limited quantities (LQ) lL• Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity 2 · Transport category · Tunnel restriction code D · IMDG · Limited quantities (LQ) lL• Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity (Contd. on page 9)



Page 9/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.11.2016

Version number 58

Revision: 02.11.2016

(Contd. of page 8)

Trade name: PETEC High-Performance PTFE-Spray

· UN ''Model Regulation'':

UN 1950 AEROSOLS. 2.1

### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 28, 29
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols - Category 1 Press. Gas C: Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 • \* Data compared to the previous version altered.