

PETEC Verbindungstechnik GmbH | Wüstenbuch 26 | D-96132 Schlüsselfeld Tel.: +49 95 55 / 80 99 40 | Fax: +49 95 55 / 80 99 425 | info@petec.de www.petec.de

# **BODY CAVITY PROTECTION & CONSERVATION, TRANSLUCENT**

Offers optimum protection against stone chips and rust in all corrosive environments with very good adhesion to metallic surfaces. Bitumen underbody protection forms a permanent, visco-elastic and closed protective film with anti-buzzing effect.

## **CHARACTERISTICS**

- long-term corrosion protection for body cavities
- quick-drying, long-lasting plastic protective film
- infiltrates and suppresses moisture
- very good penetration ability, hard-to-reach body cavities are also reached
- high heat resistance and good cold flexibility
- resistant to water, salt water, brake fluid and many chemicals

## **TECHNICAL DATA**

colour	translucent
base	oil and paraffin wax
processing temperature	+5°C to +30°C
shelf life	36 months; store in a cool and dry place

#### INSTRUCTIONS FOR USE SPRAY

Shake well before use. Spray PETEC body cavity protection & conservation on the rust-free, clean, dry and degreased surface. After use, turn the can upside down and spray until the valve is empty.

# **INSTRUCTIONS FOR USE VACUUM CAN**

Shake well before use. Spray PETEC body cavity protection & conservation on the rust-free, clean, dry and degreased surface using the PETEC underbody protection gun (art. no. 98507) and screw on the hose if necessary. Clean the underbody protection gun after use.

Observe the safety and technical datasheet! (Download PETEC data sheets from www.petec.de)

# **CONTAINER SIZE**

