

Printing date 14.11.2016 Version number 19 Revision: 14.11.2016

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: PETEC Welding And Separating Protection Spray
- · Article number: 72050
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Coating
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

PETEC Verbindungstechnik GmbH

Wüstenbuch 26

96132 Schlüsselfeld / Deutschland

Telefon +49 (0) 9555 80994-0

Fax +49 (0) 9555 80994-25

Homepage www.petec.de

E-Mail: info@petec.de

- · Further information obtainable from: Technische Auskunft: info@petec.de
- 1.4 Emergency telephone number: Telefon +49 (0) 9555 80994-0

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Aerosol 3 H229 Pressurised container: May burst if heated.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07

GHS08

- · Signal word Warning
- · Hazard-determining components of labelling: dichloromethane
- · Hazard statements

H229 Pressurised container: May burst if heated.

(Contd. on page 2)



Printing date 14.11.2016 Version number 19 Revision: 14.11.2016

#### Trade name: PETEC Welding And Separating Protection Spray

(Contd. of page 1)

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P251 Do not pierce or burn, even after use. P260 Do not breathe vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

*P280* Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention. P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501 Dispose of contents/container to hazardous or special waste collection point.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

	· Dangerous components:		
	CAS: 75-09-2	dichloromethane	50-<100%
	EINECS: 200-838-9	& Carc. 2, H351; STOT RE 2, H373; 🗘 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335-H336	
	Reg.nr.: 02-2119752537-31-xxx	Eye Irrit. 2, H319; STOT SE 3, H335-H336	
Γ	CAS: 124-38-9	carbon dioxide	2.5-<5%
	EINECS: 204-696-9	♦ Press. Gas L, H280	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)





Printing date 14.11.2016 Version number 19 Revision: 14.11.2016

Trade name: PETEC Welding And Separating Protection Spray

(Contd. of page 2)

· After swallowing:

Do not induce vomiting; call for medical help immediately.

Administer medicinal carbon.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot \textit{4.3 Indication of any immediate medical attention and special treatment needed} \\$

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

• **6.4 Reference to other sections** See Section 13 for disposal information.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin and eyes.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)





Printing date 14.11.2016 Version number 19 Revision: 14.11.2016

Trade name: PETEC Welding And Separating Protection Spray

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- $\cdot$  7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 75-09-2 dichloromethane

WEL Short-term value: 1060 mg/m³, 300 ppm

Long-term value:  $350 \text{ mg/m}^3$ , 100 ppm

BMGV, Sk

CAS: 124-38-9 carbon dioxide

WEL Short-term value: 27400 mg/m³, 15000 ppm Long-term value: 9150 mg/m³, 5000 ppm

· Ingredients with biological limit values:

#### CAS: 75-09-2 dichloromethane

BMGV 30 ppm

Medium: end-tidal breath Sampling time: post shift Parameter: carbon monoxide

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- $\cdot \textit{General protective and hygienic measures:} \\$

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Fluorocarbon rubber (Viton)

Recommended thickness of the material:  $\geq 0.7$  mm

· Penetration time of glove material

≥60 min

(Contd. on page 5)





Printing date 14.11.2016 Version number 19 Revision: 14.11.2016

Trade name: PETEC Welding And Separating Protection Spray

(Contd. of page 4)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

#### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol
Colour: Colourless
• Odour: Sweetish

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· Flash point: Not applicable, as aerosol.

• Ignition temperature:  $>200 \, ^{\circ}C$ 

· Danger of explosion: Product does not present an explosion hazard.

• **Density at 20 °C:** 1.29291 g/cm<sup>3</sup>

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

 Organic solvents:
 89.7 %

 VOC (EC)
 1159.9 g/l

• 9.2 Other information No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

Reacts with acids, alkalis and oxidising agents.

Reacts violently with oxidising agents.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Hydrogen chloride (HCl)

Phosgen

(Contd. on page 6)



Printing date 14.11.2016 Version number 19 Revision: 14.11.2016

Trade name: PETEC Welding And Separating Protection Spray

(Contd. of page 5)

Carbon monoxide and carbon dioxide

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 1783 mg/kg (rat)

CAS: 75-09-2 dichloromethane

 Oral
 LD50
 1600 mg/kg (rat)

 Inhalative
 LC50/4 h
 88 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

Suspected of causing cancer.

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

- · STOT-repeated exposure
- May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.

#### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

GB



Printing date 14.11.2016 Version number 19 Revision: 14.11.2016

Trade name: PETEC Welding And Separating Protection Spray

(Contd. of page 6)

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

16 05 04\* gases in pressure containers (including halons) containing hazardous substances

15 01 04 metallic packaging

· ADR,RID,ADN, IMDG, IATA

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR,RID,ADN, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
· ADR/RID/ADN	UN1950 AEROSOLS
· IMDG	AEROSOLS
· IATA	AEROSOLS, non-flammable, containing substances Division 6.1, Packing Group III
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN	
· Class · Label	2 5T Gases. 2.2+6.1
· IMDG	
· Class	2.2
· Label	2.2/6.1
· IATA	
2	
· Class	2.2
· Label	2.2 (6.1)

Void



Printing date 14.11.2016 Version number 19 Revision: 14.11.2016

Trade name: PETEC Welding And Separating Protection Spray

	(Contd. of page
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Gases.
· Danger code (Kemler):	-
· EMS Number:	F- $D$ , $S$ - $U$
· Stowage Code	SW1 Protected from sources of heat.
-	SW22 For AEROSOLS with a maximum capacity of 1 litro
	Category A. For AEROSOLS with a capacity above 1 litro
	Category B. For WASTE AEROSOLS: Category C, Clea
	of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litro
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4. For AEROSOLS with a capacit
	above 1 litre: Segregation as for the appropriate
	subdivision of class 2. For WASTE AEROSOLS
	Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Ani	nex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN	
· Limited quantities (LQ)	120 ml
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	1
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 59
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

(Contd. on page 9)





Printing date 14.11.2016 Version number 19 Revision: 14.11.2016

Trade name: PETEC Welding And Separating Protection Spray

(Contd. of page 8)

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Aerosol 3: Aerosols – Category 3

Press. Gas L: Gases under pressure - Liquefied gas

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

\* \* Data compared to the previous version altered.

GB